

# AGRIMAX RT 955

<b>TIRE SIZE</b>	<b>270/95 R 36</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ОПРЫСКИВАТЕЛЬ / КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	139 A8/B



## РАЗМЕРЫ IS STANDARD

<b>SW (MM)</b>	275	<b>RIM REC</b>	W 9
<b>OD (MM)</b>	1428	<b>RIM ALT</b>	W 8; W 10
<b>SLR (MM)</b>	665	<b>ECE</b>	E4-106R-000659
<b>RC (MM)</b>	4335	<b>SRI</b>	675

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.4
50	950	1240	1510	1655	1750	1920	2090	2260	2430	-
40	950	1240	1510	1655	1750	1920	2090	2260	2430	-
30	1020	1330	1620	1775	1880	2060	2245	2425	2605	-
10	1130	1425	1750	2080	2410	2480	2775	3065	3355	3645

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.