


# AGRIMAX RT 855

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>280/85 R 20</b>   |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL           |
| <b>MACHINERY</b>    | FELDSPRITZE /<br>TRAUBENERNTEMASCHINE /<br>TRACTOR / ERNTEMASCHINE /<br>LANDWIRTSCHAFTLICHE GERÄTE |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 122 A8/B   |



## ABMESSUNGEN IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 292  | <b>RIM REC</b> | W 10            |
| <b>OD (MM)</b>  | 984  | <b>RIM ALT</b> | W 9             |
| <b>SLR (MM)</b> | 447  | <b>ECE</b>     | E11-106R-007936 |
| <b>RC (MM)</b>  | 2977 | <b>SRI</b>     | 475             |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR   | 0.6 | 0.8 | 1.0  | 1.2  | 1.4  | 1.6  | 2.0  | 2.4  |
|--------------|-----|-----|------|------|------|------|------|------|
| <b>50</b>    | 615 | 720 | 825  | 930  | 1035 | 1125 | 1335 | 1500 |
| <b>40</b>    | 615 | 720 | 825  | 930  | 1035 | 1125 | 1335 | 1500 |
| <b>30</b>    | 660 | 775 | 885  | 1000 | 1110 | 1205 | 1430 | 1605 |
| <b>10 LT</b> | 825 | 965 | 1110 | 1250 | 1390 | 1510 | 1790 | 2010 |
| <b>10 HT</b> | 660 | 775 | 885  | 1000 | 1110 | 1205 | 1430 | 1605 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.