


RIDEMAX FL 690

| | |
|---------------------|--|
| TIRE SIZE | 30.5L R 32 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TANKWAGEN / ANHÄNGER / LANDWIRTSCHAFTLICHE GERÄTE / ANHÄNGER |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 184 A8 ; 181 B |



ABMESSUNGEN US STANDARD

| | | | |
|-----------------|----------|----------------|-----------------|
| USA-CODE | 94033836 | RC (IN) | 213.8 |
| SW (IN) | 31.1 | RIM REC | DH 27 B |
| OD (IN) | 70.9 | RIM ALT | DW 27 B |
| SLR (IN) | 31.7 | ECE | E11-106R-002986 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 12 | 15 | 20 | 23 | 29 | 35 | 41 | 44 |
|-----------|-------|-------|-------|-------|-------|-------|-------|-------|
| 30 | 8370 | 9640 | 11640 | 12550 | 14370 | 16000 | 17460 | 18190 |
| 25 | 9630 | 11090 | 13390 | 14440 | 16530 | 18420 | 20090 | 20920 |
| 20 | 10880 | 12530 | 15130 | 16320 | 18680 | 20810 | 22710 | 23640 |
| 15 | 11470 | 13220 | 15960 | 17210 | 19700 | 21930 | 23930 | 24920 |
| 5 | 13320 | 15330 | 18520 | 19960 | 22850 | 25460 | 27780 | 28920 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.