


RIDEMAX FL 693 M



TIRE SIZE	650/50 R 22.5
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	CAMIÓN CISTERNA / REMOLQUE / MAQUINARIA AGRÍCOLA
VERSIÓN	STANDARD
TIRE TYPE	TL
LI/SS	163 D ; 160 E

DIMENSIONES US STANDARD

CÓDIGO USA	94043019	RC (IN)	146.3
SW (IN)	25.4	RIM REC	AG 20.00
OD (IN)	48.1	ECE	E4-106R-001417
SLR (IN)	21.1		

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	15	17	23	29	35	41	46	52	58
45	3630	4070	5060	5750	6650	7540	8230	9030	9920
40	3920	4410	5490	6240	7210	8170	8930	9790	10750
30	4750	5330	6640	7550	8720	9890	10800	11840	13010
25	5350	6000	7460	8490	9800	11110	12140	13300	14620
15	6210	6970	8660	9850	11390	12920	14110	15460	16990
5	7070	7940	9880	11220	12960	14700	16060	17610	19340

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.