

XL GRIP (L3)



XL GRIP (L3)



XL GRIP (E-3/L-3) is a wide-base bias-ply tire for loaders designed to minimize cuts and punctures in heavy-duty loading applications. It provides exceptional traction as well as an extended tire life.



	SIZE	TT/TL	PR	LI/SS	RIM		O.W. (in)	OD (in)	SLR (in)	RC (in)	VERSION
					REC RIM	ALT RIM					
											
Ø20"	16.0/70 -20	TL	16	-	13 SDC	-	15.9	42.9	18.9	129.7	STD
Ø25"	17.5 - 25	TL	20	-	14.00/1.5	-	17.1	53.0	24.5	156.7	DB
	26.5 - 25	TL	28	-	22.00/3.0	-	26.8	68.5	31.3	202.8	STD
	17.5 - 25	TT	20	-	14.00/1.5	-	17.1	53.0	24.5	156.7	DB
	23.5 - 25	TL	20	-	19.50/2.5	-	23.6	64.0	29.2	189.4	STD

DB: DUAL BEAD, STD: STANDARD, AB HD: ARAMID BELTED HD

TECHNOLOGIES		PERFORMANCES	
			
			
-	-	Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index	

SIZE	TT/TL	PR	LI/SS	RIM		O.W. (in)	OD (in)	SLR (in)	RC (in)	VERSION
				REC RIM	ALT RIM					
										
29.5 - 25	TL	32	-	25.00/3.5	-	29.9	73.2	33.4	218.3	STD
20.5 - 25	TL	24	-	17.00/2.0	-	20.9	58.5	26.9	173.0	STD
20.5 - 25	TL	12	-	17.00/2.0	-	20.9	58.5	26.9	173.0	STD
26.5 - 25	TL	32	-	22.00/3.0	-	26.8	68.5	31.3	202.8	STD
15.5 - 25	TL	12	-	12.00/1.3	12.00/1.3 (DC)	15.8	50.6	22.6	148.3	STD
17.5 - 25	TL	16	-	14.00/1.5	-	17.1	53.0	24.5	156.7	STD
29.5 - 25	TL	28	-	25.00/3.5	-	29.9	73.2	33.4	218.3	STD
17.5 - 25	TL	24	-	14.00/1.5	-	17.1	53.0	24.5	156.7	DB
17.5 - 25	TL	20	-	14.00/1.5	-	17.1	53.0	24.5	156.7	STD
26.5 - 25	TL	20	-	22.00/3.0	-	26.8	68.5	31.3	202.8	STD

DB: DUAL BEAD, STD: STANDARD, AB HD: ARAMID BELTED HD

TECHNOLOGIES		PERFORMANCES	
			Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

SIZE	TT/TL	PR	LI/SS	RIM		O.W. (in)	OD (in)	SLR (in)	RC (in)	VERSION
				REC RIM	ALT RIM					
										
23.5 - 25	TL	16	-	19.50/2.5	-	23.6	64.0	29.2	189.4	STD
17.5 - 25	TL	12	-	14.00/1.5	-	17.1	53.0	24.5	156.7	STD
20.5 - 25	TL	20	-	17.00/2.0	-	20.9	58.5	26.9	173.0	STD
20.5 - 25	TL	16	-	17.00/2.0	-	20.9	58.5	26.9	173.0	STD
23.5 - 25	TL	24	-	19.50/2.5	-	23.6	64.0	29.2	189.4	AB HD
23.5 - 25	TL	24	-	19.50/2.5	-	23.6	64.0	29.2	189.4	STD

DB: DUAL BEAD, STD: STANDARD, AB HD: ARAMID BELTED HD

TECHNOLOGIES		PERFORMANCES	
			Permissible tolerances: 0.0. 2%—S.W. 2%—RC 2.5%—LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index
			