


# AS 504

<b>TIRE SIZE</b>	<b>16.0/70 - 20</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / ПРИЦЕП ДЛЯ ПОЛЕВЫХ РАБОТ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	142 A8
<b>LI/SS FREE ROLLING</b>	154 A8



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94019069	<b>RC (IN)</b>	126.5
<b>SW (IN)</b>	16.5	<b>RIM REC</b>	13
<b>OD (IN)</b>	43.2	<b>RIM ALT</b>	12 SDC; 14; 13 SDC
<b>SLR (IN)</b>	19.2	<b>ECE</b>	E4-106R-001876

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	51
5 FR	11570
15 FR	9840
20 FR	9260
25 FR	8270
5 DW	8180
15 DW	6960
20 DW	6550
25 DW	5840

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.