


RIDEMAX FL 693 M

| | |
|---------------------|--|
| TIRE SIZE | 650/65 R 30.5 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TANKBIL / SLÄPVAGN / ARBETSFORDON |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 176 D |



DIMENSIONER IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 645 | RIM REC | AG 20.00 |
| OD (MM) | 1623 | ECE | E11-106R-009076 |
| SLR (MM) | 734 | SRI | 775 |
| RC (MM) | 4939 | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.8 | 1.0 | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.6 | 4.0 |
|------------|------|------|------|------|------|------|------|-------|-------|-------|
| 70 | 2070 | 2395 | 2720 | 3300 | 3815 | 4400 | 4980 | 5370 | 5950 | 6465 |
| 65 | 2275 | 2630 | 2985 | 3625 | 4190 | 4830 | 5470 | 5895 | 6535 | 7100 |
| 50 | 2755 | 3185 | 3610 | 4385 | 5075 | 5845 | 6620 | 7135 | 7910 | 8595 |
| 40 | 3095 | 3580 | 4060 | 4930 | 5700 | 6570 | 7440 | 8020 | 8890 | 9660 |
| 25 | 3595 | 4155 | 4715 | 5725 | 6620 | 7630 | 8640 | 9315 | 10325 | 11220 |
| 10 | 4090 | 4730 | 5370 | 6520 | 7545 | 8695 | 9845 | 10610 | 11760 | 12780 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.