

# AGRIMAX RT 765

<b>TIRE SIZE</b>	<b>710/70 R 42</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	PULVERIZADOR AGRÍCOLA / TRATOR / VINDIMADORA / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS
<b>VERSÃO</b>	SPECIAL
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	176 D ; 179 A8



## DIMENSÕES US STANDARD

<b>CÓDIGO USA</b>	94063550	<b>RC (IN)</b>	243.1
<b>SW (IN)</b>	28.2	<b>RIM REC</b>	DW 23 B
<b>OD (IN)</b>	81.1	<b>RIM ALT</b>	DW 25 B
<b>SLR (IN)</b>	36.3	<b>ECE</b>	E11-106R-006001

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35	41
40	6730	7830	8930	10020	11120	12210	13470	14250	15650
30	7080	8220	9370	10530	11670	12820	14140	14960	16430
25	7350	8540	9740	10930	12140	13330	14690	15550	17080
20	7750	9010	10260	11530	12790	14040	15490	16390	18000
5 LT	9030	10490	11960	13430	14900	16370	18040	19090	20980
5 HT	7750	9010	10260	11530	12790	14040	15490	16390	18000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.