

# AW 729

<b>TIRE SIZE</b>	<b>340/55 - 16</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	EMPACADORA DE HENO / MAQUINARIA AGRÍCOLA / REMOLQUE / COSECHADORA / MAQUINARIA AGRÍCOLA
<b>VERSIÓN</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	121 A8
<b>LI/SS FREE ROLLING</b>	133 A8



## DIMENSIONES US STANDARD

<b>CÓDIGO USA</b>	94066117	<b>RC (IN)</b>	92.8
<b>SW (IN)</b>	13.5	<b>RIM REC</b>	11.0
<b>OD (IN)</b>	30.9	<b>ECE</b>	E11-106R-006421
<b>SLR (IN)</b>	14.1		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	46
5 FR	6360
15 FR	5400
20 FR	5080
25 FR	4540
5 DW	4475
15 DW	3805
20 DW	3580
25 DW	3200

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.