


FL 630 SUPER

| | |
|---------------------|--|
| TIRE SIZE | 580/65 R 22.5 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | ESPARCIDOR / CAMIÓN CISTERNA / REMOLQUE / MAQUINARIA AGRÍCOLA |
| VERSIÓN | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 174 D |



DIMENSIONES US STANDARD

| | | | |
|-------------------|----------|----------------|------------------------------|
| CÓDIGO USA | 94073221 | RC (IN) | 159.8 |
| SW (IN) | 22.9 | RIM REC | AG 18.00 |
| OD (IN) | 52.2 | RIM ALT | AG 16.00; AG 17.00; AG 20.00 |
| SLR (IN) | 23.4 | ECE | E11-106R-008289 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 17 | 23 | 29 | 35 | 41 | 46 | 52 | 58 | 65 | 73 | 80 | 87 |
|-----------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 45 | 4310 | 5380 | 6050 | 7000 | 7940 | 8740 | 9560 | 10490 | 11170 | 11840 | 12640 | 13450 |
| 40 | 4730 | 5910 | 6650 | 7680 | 8720 | 9600 | 10490 | 11530 | 12270 | 13010 | 13890 | 14770 |
| 30 | 5730 | 7150 | 8050 | 9300 | 10550 | 11630 | 12700 | 13950 | 14850 | 15740 | 16810 | 17880 |
| 25 | 6440 | 8050 | 9050 | 10450 | 11860 | 13060 | 14270 | 15670 | 16690 | 17690 | 18890 | 20090 |
| 15 | 7470 | 9350 | 10520 | 12150 | 13780 | 15180 | 16580 | 18220 | 19380 | 20550 | 21950 | 23350 |
| 5 | 8510 | 10640 | 11970 | 13830 | 15700 | 17280 | 18880 | 20740 | 22070 | 23400 | 25000 | 26590 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.