


# SR 234

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>VF 445/50 R 22.5</b>  |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL           |
| <b>MACHINERY</b>    | ENFARDADEIRA DE FENO / CEIFEIRA /<br>IMPLEMENTOS AGRÍCOLAS /<br>REBOQUE / IMPLEMENTOS<br>AGRÍCOLAS |
| <b>VERSÃO</b>       | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 167 D  |



## DIMENSÕES US STANDARD

|                   |          |                 |                  |
|-------------------|----------|-----------------|------------------|
| <b>CÓDIGO USA</b> | 94512799 | <b>RIM REC</b>  | 14.00            |
| <b>OD (IN)</b>    | 40.1     | <b>ECE</b>      | E11-106R-0010963 |
| <b>SLR (IN)</b>   | 17.8     | <b>TRA CODE</b> | I2               |
| <b>RC (IN)</b>    | 120.1    |                 |                  |

## LOAD CAPACITY (LBS/TIRE)

|                |           |
|----------------|-----------|
| <b>MPH/PSI</b> | <b>98</b> |
| 40             | 12000     |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.