

# POWER TRAX

|              |                                                         |
|--------------|---------------------------------------------------------|
| TYRE SIZE    | 12.00 - 20                                              |
| UM           | IS STANDARD                                             |
| CONSTRUCTION | BIAS                                                    |
| MACHINERY    | EMPTY CONTAINER HANDLER /<br>UNDERGROUND MINING VEHICLE |
| VERSION      | STANDARD                                                |
| TL/TT        | TT                                                      |
| LI/SS        | 176 A5                                                  |



## DIMENSIONS IS STANDARD

|         |      |    |    |
|---------|------|----|----|
| SW (MM) | 320  | PR | 20 |
| OD (MM) | 1150 |    |    |
| RIM REC | 8.5  |    |    |
| RIM ALT | 9.0  |    |    |

## LOAD CAPACITY (KG/TYRE)

| KM/H / BAR         | 10.00 |
|--------------------|-------|
| 25 LOAD WHEEL      | 9230  |
| 25 STEER WHEEL     | 7100  |
| 10 OTHER VEHICLES  | 9230  |
| 25 OTHER VEHICLES  | 7100  |
| STATIC SIDE LOADER | 10720 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.