

ROCK GRIP E4



ROCK GRIP E4

ROCK GRIP (E-4) is a bias-ply tyre specially designed for haul trucks in mining service and quarry operations. Whenever your short-haul site conditions require both heat resistance and cut protection, ROCK GRIP is the tyre you can rely upon.



	SIZE	TT/TL	TRA CODE	PR	LI/SS	RIM		TKPH (TK/H)	OW (MM) (mm)	OD (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (MM)	VERSION
						REC RIM	ALT RIM							
														
Ø25"	18.00 - 25	TT	E4	32	-	13.00/2.5	15.00/2.5	0	510	1650	753	4885	54,5	STD
	18.00 - 25	TL	E4	36	-	13.00/2.5	15.00/2.5	0	510	1650	753	4885	54,5	STD
	14.00 - 25	TT	E4	24	-	10.00/2.0	-	0	375	1410	649	4173	50,5	STD
	14.00 - 25	TL	E4	24	-	10.00/2.0	-	0	375	1410	649	4173	50,5	STD

STD: STANDARD, CR: CUT RESISTANT COMPOUND, SB: STEEL BELTED

TECHNOLOGIES			PERFORMANCES		
					
					

Permissible tolerances: O.O. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026

SIZE	TT/TL	TRA CODE	PR	LI/SS	RIM		TKPH (TK/H)	OW (MM) (mm)	OD (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (MM)	VERSION
					REC RIM	ALT RIM							
													
18.00 - 25	TL	E4	40	-	13.00/2.5	15.00/2.5	0	510	1650	753	4885	54,5	STD
16.00 - 25	TL	E4	32	-	11.25/2.0	13.00/2.0	0	470	1525	699	4514	51,5	STD
14.00 - 25	TL	E4	28	-	10.00/2.0	-	0	375	1410	649	4173	50,5	STD
14.00 - 25	TL	E4	24	-	10.00/1.5	-	0	375	1410	649	4173	50,5	STD
14.00 - 25	TL	E4	28	-	10.00/1.5	-	0	375	1410	649	4173	50,5	STD
18.00 - 25	TT	E4	40	-	13.00/2.5	15.00/2.5	0	510	1650	753	4885	54,5	STD
18.00 - 25	TT	E4	24	-	13.00/2.5	15.00/2.5	0	510	1650	753	4885	54,5	STD
18.00 - 25	TL	E4	32	-	13.00/2.5	15.00/2.5	0		1650	753	4885	54,5	STD
14.00 - 25	TT	E4	28	-	10.00/2.0	-	0	375	1410	649	4173	50,5	STD

STD: STANDARD, CR: CUT RESISTANT COMPOUND, SB: STEEL BELTED

TECHNOLOGIES			PERFORMANCES		
					
					

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026

SIZE	TT/TL	TRA CODE	PR	LI/SS	RIM		TKPH (TK/H)	OW (MM) (mm)	OD (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (MM)	VERSION
					REC RIM	ALT RIM							
													
16.00 - 25	TL	E4	28	-	11.25/2.0	13.00/2.0	0	470	1525	699	4514	51,5	STD
14.00 - 25	TL	E4	32	-	10.00/2.0	-	0	375	1410	649	4173	50,5	STD
14.00 - 25	TT	E4	24	-	10.00/1.5	-	0	375	1410	649	4173	50,5	STD
18.00 - 25	TT	E4	40	-	13.00/2.5	15.00/2.5	0	510	1650	753	4885	54,5	CR
14.00 - 25	TT	E4	28	-	10.00/1.5	-	0	375	1410	649	4173	50,5	STD
14.00 - 25	TL	E4	32	-	10.00/1.5	-	0	375	1410	649	4173	50,5	STD
16.00 - 25	TL	E4	32	-	11.25/2.0	13.00/2.0	0	470	1525	699	4514	51,5	SB
18.00 - 33	TT	E4	36	-	13.00/2.5	-	0	510	1887	869	5586	59,5	STD
18.00 - 33	TL	E4	36	-	13.00/2.5	-	0	510	1887	869	5586	59,5	STD

STD: STANDARD, CR: CUT RESISTANT COMPOUND, SB: STEEL BELTED

TECHNOLOGIES			PERFORMANCES		
					
					

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026

SIZE	TT/TL	TRA CODE	PR	LI/SS	RIM		TKPH (TK/H)	OW (MM) (mm)	OD (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (MM)	VERSION
					REC RIM	ALT RIM							
													
18.00 - 33	TL	E4	40	-	13.00/2.5	-	0	510	1887	869	5586	59,5	STD
18.00 - 33	TL	E4	44	-	13.00/2.5	-	0	510	1887	869	5586	59,5	STD
18.00 - 33	TT	E4	40	-	13.00/2.5	-	0	510	1887	869	5586	59,5	STD
18.00 - 33	TL	E4	36	-	13.00/2.5	-	0	510	1887	869	5586	59,5	CR
18.00 - 33	TL	E4	40	-	13.00/2.5	-	0	510	1887	869	5586	59,5	CR
21.00 - 35	TL	E4	40	-	15.00/3.0	-	0	580	2040	943	6068	59,5	STD
24.00 - 35	TL	E4	48	-	17.00/3.5	-	0	655	2190	1003	6482	61,5	STD
21.00 - 35	TL	E4	40	-	15.00/3.0	-	0	580	2040	943	6068	59,5	CR
24.00 - 35	TL	E4	48	-	17.00/3.5	-	0	655	2190	1003	6482	61,5	CR

STD: STANDARD, CR: CUT RESISTANT COMPOUND, SB: STEEL BELTED

TECHNOLOGIES			PERFORMANCES		
					
		-	-	-	-

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026

	SIZE	TT/TL	TRA CODE	PR	LI/SS	RIM		TKPH (TK/H)	OW (MM) (mm)	OD (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (MM)	VERSION
						REC RIM	ALT RIM							
														
	21.00 - 35	TL	E4	36	-	15.00/3.0	-	0	580	2040	943	6068	59,5	CR
	21.00 - 35	TL	E4	36	-	15.00/3.0	-	0	580	2040	943	6068	59,5	STD
Ø49"	24.00 - 49	TL	E4	42	-	17.00/3.5	-	0	655	2531	1184	7498	61,5	STD
	24.00 - 49	TL	E4	48	-	17.00/3.5	-	0	655	2531	1184	7498	61,5	STD
	24.00 - 49	TL	E4	48	-	17.00/3.5	-	0	655	2531	1184	7498	61,5	CR
	30.00 - 51	TL	E4	52	-	22.00/4.5	-	0	830	2910	1350	8615	72	CR
	30.00 - 51	TL	E4	46	-	22.00/4.5	-	0	830	2910	1350	8615	71,5	STD
	30.00 - 51	TL	E4	52	-	22.00/4.5	-	0	830	2910	1350	8615	71,5	STD

STD: STANDARD, CR: CUT RESISTANT COMPOUND, SB: STEEL BELTED

TECHNOLOGIES			PERFORMANCES		
					
					

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026



TECHNOLOGIES		PERFORMANCES
  E4   -		  

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. BKT reserves the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026