

# AW 909

<b>TIRE SIZE</b>	10.0/75 - 15.3
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	❖ BIAS
<b>MACHINERY</b>	ПРЕСС-ПОДБОРЩИК / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ПРИЦЕП / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS FREE ROLLING</b>	130 A8



## РАЗМЕРЫ IS STANDARD

<b>SW (MM)</b>	274	<b>RIM REC</b>	9.00
<b>OD (MM)</b>	760	<b>ECE</b>	E4-106R-001544
<b>SLR (MM)</b>	343	<b>PR</b>	14
<b>RC (MM)</b>	2227		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	5.50
10 FR	2660
25 FR	2260
30 FR	2130
40 FR	1900

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.