


# AGRIMAXFACTOR

<b>TIRE SIZE</b>	<b>480/70 R 24</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRACTOR
<b>VERSION</b>	STANDARD
<b>TL/TT</b>	TL
<b>LI/SS</b>	138 D ; 141 A8



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	485	<b>RIM REC</b>	W 15 L
<b>OD (MM)</b>	1311	<b>RIM ALT</b>	W 14 L ; W 16 L
<b>SLR (MM)</b>	590	<b>ECE</b>	E11-106R-0011157
<b>RC (MM)</b>	3895	<b>SRI</b>	625

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6
65	1300	1515	1725	1940	2150	2360
50	1365	1590	1815	2035	2260	2480
40	1425	1655	1890	2120	2355	2575
30	1495	1740	1985	2230	2475	2715
10 LT	1745	2030	2315	2600	2885	3165
10HT	1495	1740	1985	2230	2475	2715

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.