


# AS 504

|                           |  |
|---------------------------|--|
| <b>TIRE SIZE</b>          | <b>24X8.50 - 12</b>  |
| <b>UM</b>                 | IS STANDARD  |
| <b>CONSTRUCTION</b>       |  BIAS |
| <b>MACHINERY</b>          | TELESKOPLADER / FELD-ANHÄNGER /<br>LANDWIRTSCHAFTLICHE GERÄTE /<br>TELESKOPLADER       |
| <b>VERSION</b>            | STANDARD   |
| <b>TIRE TYPE</b>          | TL   |
| <b>LI/SS DRIVE WHEEL</b>  | 81 A8  |
| <b>LI/SS FREE ROLLING</b> | 94 A8  |



## ABMESSUNGEN IS STANDARD

|                 |      |                |                  |
|-----------------|------|----------------|------------------|
| <b>SW (MM)</b>  | 216  | <b>RIM REC</b> | 7 JA; 7.00 I     |
| <b>OD (MM)</b>  | 610  | <b>ECE</b>     | E11-106R-0010452 |
| <b>SLR (MM)</b> | 284  | <b>PR</b>      | 6                |
| <b>RC (MM)</b>  | 1761 |                |                  |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 2.30 |
|------------|------|
| 10 FR      | 940  |
| 25 FR      | 795  |
| 30 FR      | 750  |
| 40 FR      | 670  |
| 10 DW      | 645  |
| 25 DW      | 550  |
| 30 DW      | 515  |
| 40 DW      | 462  |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.