


# AGRIMAX RT 765M

<b>TIRE SIZE</b>	<b>710/70 R 38</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	FELDSPRITZE / TRACTOR / TRAUBENERNTEMASCHINE / ERNTEMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	175 D ; 178 A8



## ABMESSUNGEN US STANDARD

<b>USA-CODE</b>	94066797	<b>RC (IN)</b>	226.4
<b>SW (IN)</b>	28.2	<b>RIM REC</b>	DW 23 B
<b>OD (IN)</b>	77.1	<b>ECE</b>	E11-106R-004072
<b>SLR (IN)</b>	33.8	<b>TRA CODE</b>	R1W

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
40	6380	7330	8410	9490	10580	11660	12750	13560
30	6700	7690	8840	9980	11110	12260	13390	14240
25	6940	7980	9160	10340	11530	12710	13890	14770
20	7340	8430	9680	10920	12170	13410	14670	15600
5 LT	8550	9820	11280	12730	14190	15640	17100	18180
5 HT	7340	8430	9680	10920	12170	13410	14670	15600

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.