


FL 630 SUPER

| | |
|---------------------|--|
| TIRE SIZE | 600/50 R 22.5 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | SPARGITORE / AUTOBOTTE / RIMORCHIO / ATTREZZI AGRICOLI |
| VERSIONE | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 159 D |



DIMENSIONI US STANDARD

| | | | |
|-------------------|----------|----------------|-----------------|
| CODICE USA | 94060900 | RC (IN) | 139.1 |
| SW (IN) | 24.1 | RIM REC | AG 20.00 |
| OD (IN) | 46.1 | ECE | E11-106R-005992 |
| SLR (IN) | 20.4 | | |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 15 | 17 | 23 | 29 | 35 | 41 | 46 | 52 | 58 |
|-----------|------|------|------|-------|-------|-------|-------|-------|-------|
| 45 | 3210 | 3600 | 4490 | 5100 | 5890 | 6680 | 7300 | 8000 | 8780 |
| 40 | 3530 | 3960 | 4930 | 5600 | 6470 | 7330 | 8010 | 8780 | 9645 |
| 30 | 4270 | 4790 | 5960 | 6780 | 7830 | 8870 | 9690 | 10630 | 11670 |
| 25 | 4790 | 5380 | 6690 | 7620 | 8800 | 9980 | 10890 | 11940 | 13120 |
| 15 | 5570 | 6260 | 7780 | 8850 | 10220 | 11600 | 12650 | 13880 | 15240 |
| 5 | 6340 | 7120 | 8860 | 10070 | 11640 | 13190 | 14420 | 15810 | 17360 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.