


# TF 9090

|                     |                                                                                        |
|---------------------|----------------------------------------------------------------------------------------|
| <b>TIRE SIZE</b>    | 5.50 - 16                                                                              |
| <b>UM</b>           | IS STANDARD                                                                            |
| <b>CONSTRUCTION</b> |  BIAS |
| <b>MACHINERY</b>    | MINITRACTOR / TRACTOR /<br>REMOLQUE                                                    |
| <b>VERSIÓN</b>      | STANDARD                                                                               |
| <b>TIRE TYPE</b>    | TT                                                                                     |
| <b>LI/SS</b>        | 86 A6                                                                                  |



## DIMENSIONES IS STANDARD

|                 |      |                |                |
|-----------------|------|----------------|----------------|
| <b>SW (MM)</b>  | 150  | <b>RIM REC</b> | 4.00 E         |
| <b>OD (MM)</b>  | 710  | <b>RIM ALT</b> | 3.50 D; 4.50 E |
| <b>SLR (MM)</b> | 332  | <b>ECE</b>     | E4-106R-001955 |
| <b>RC (MM)</b>  | 2116 | <b>PR</b>      | 6              |

## LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>3.70</b> |
| 30                | 530         |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.