

# FLOTATION 648

<b>TIRE SIZE</b>	<b>650/65 - 30.5</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	ПРЕСС-ПОДБОРЩИК / КОМБАЙН / РАЗБРАСЫВАТЕЛЬ / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
<b>VERSION</b>	HD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	167 A8/163 B
<b>LI/SS FREE ROLLING</b>	179 A8/175 B



## РАЗМЕРЫ IS STANDARD

<b>SW (MM)</b>	670	<b>RIM REC</b>	AG 20.00
<b>OD (MM)</b>	1660	<b>ECE</b>	E11-106R-004562
<b>SLR (MM)</b>	710	<b>PR</b>	16
<b>RC (MM)</b>	4935		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.80	2.00	2.20
10 FR	9645	10260	10850
20 FR	8680	9235	9765
30 FR	7715	8210	8680
40 FR	6890	7330	7750
50 FR	6200	6595	6900
10 DW	6785	7215	7630
20 DW	6105	6495	6865
30 DW	5425	5775	6105
40 DW	4845	5155	5450
50 DW	4360	4640	4875

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.