


# AGRIMAX V-FLECTO



<b>TIRE SIZE</b>	<b>VF 710/60 R 42</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	MOTORSTARK TRAKTOR / TRAKTOR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	173 D

## DIMENSIONER IS STANDARD

<b>SW (MM)</b>	710	<b>RIM REC</b>	DW 25 B
<b>OD (MM)</b>	1930	<b>RIM ALT</b>	DW 23 B; MW 25 B
<b>SLR (MM)</b>	860	<b>ECE</b>	E11-106R-002998
<b>RC (MM)</b>	5786	<b>SRI</b>	925

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6
70	3250	3785	4315	4850	5380	5915
<b>FROM 65 TO 40</b>	3575	4160	4745	5330	5915	6500
30	3645	4240	4835	5435	6030	6630
20	3715	4325	4930	5540	6150	6760
10	3930	4575	5215	5860	6505	7150
<b>*UPTO 10 CYC WITH FRONT LOADER</b>	5005	5820	6640	7460	8280	9100
10HT	3645	4240	4835	5435	6030	6630

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.