


# RIB 713

<b>TIRE SIZE</b>	<b>IF 280/70 R 15</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	IMPLEMENTOS AGRÍCOLAS / IMPLEMENTOS AGRÍCOLAS
<b>VERSÃO</b>	STUBBLE RESISTANT
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	134 D



## DIMENSÕES US STANDARD

<b>CÓDIGO USA</b>	94052721	<b>RC (IN)</b>	92.8
<b>SW (IN)</b>	11.0	<b>RIM REC</b>	W 8
<b>OD (IN)</b>	30.7	<b>ECE</b>	E11-106R-005094
<b>SLR (IN)</b>	13.7	<b>TRA CODE</b>	I1

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	15	17	20	23	29	35	41	46	52	58	64
<b>FROM 5 TO 40 MPH</b>	1710	1950	2230	2470	2700	2940	3140	3460	3740	3970	4400	4675

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.