

AS 504

| | |
|---------------------------|---|
| TIRE SIZE | 19.0/45 - 17 |
| UM | IS STANDARD |
| CONSTRUCTION | |
| MACHINERY | TELEHANDLER / FIELD TRAILER / IMPLEMENTS / TELEHANDLER |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS DRIVE WHEEL | 131 A8 |
| LI/SS FREE ROLLING | 144 A8 |



DIMENSIONS IS STANDARD

| | | | |
|-----------------|------|----------------|----------------|
| SW (MM) | 465 | RIM REC | 16.00 |
| OD (MM) | 865 | ECE | E4-106R-001814 |
| SLR (MM) | 389 | PR | 14 |
| RC (MM) | 2578 | SRI | 410 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 2.80 |
|------------|------|
| 10 FR | 3920 |
| 25 FR | 3330 |
| 30 FR | 3135 |
| 40 FR | 2800 |
| 10 DW | 2730 |
| 25 DW | 2320 |
| 30 DW | 2185 |
| 40 DW | 1950 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.