

# PRO RIB F2M

|                     |                                 |
|---------------------|---------------------------------|
| <b>TIRE SIZE</b>    | 10.00 - 16 SL                   |
| <b>UM</b>           | IS STANDARD                     |
| <b>CONSTRUCTION</b> | BIAS                            |
| <b>MACHINERY</b>    | 2WD TRACTOR / TRACTOR / TRAILER |
| <b>VERSION</b>      | STANDARD                        |
| <b>TIRE TYPE</b>    | TL                              |
| <b>LI/SS</b>        | 110 A8                          |



## DIMENSIONS IS STANDARD

|                 |      |                |                |
|-----------------|------|----------------|----------------|
| <b>SW (MM)</b>  | 275  | <b>RIM REC</b> | 8 LB           |
| <b>OD (MM)</b>  | 894  | <b>RIM ALT</b> | W 8 L          |
| <b>SLR (MM)</b> | 409  | <b>ECE</b>     | E4-106R-002666 |
| <b>RC (MM)</b>  | 2620 | <b>PR</b>      | 8              |

## LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>3.00</b> |
| 40                | 1060        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.