


# AS 504

|                           |  |
|---------------------------|--|
| <b>TIRE SIZE</b>          | <b>11.5/80 - 15.3</b>  |
| <b>UM</b>                 | IS STANDARD  |
| <b>CONSTRUCTION</b>       |  BIAS |
| <b>MACHINERY</b>          | TELEHANDLER / FIELD TRAILER /<br>IMPLEMENTS / TELEHANDLER                              |
| <b>VERSION</b>            | STANDARD   |
| <b>TIRE TYPE</b>          | TL   |
| <b>LI/SS DRIVE WHEEL</b>  | 126 A8   |
| <b>LI/SS FREE ROLLING</b> | 139 A8   |



## DIMENSIONS IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 290  | <b>RIM REC</b> | 9.00            |
| <b>OD (MM)</b>  | 867  | <b>ECE</b>     | E11-106R-003510 |
| <b>SLR (MM)</b> | 380  | <b>PR</b>      | 14              |
| <b>RC (MM)</b>  | 2540 | <b>SRI</b>     | 410             |

## LOAD CAPACITY (KG/TIRE)

| <b>KM/H / BAR</b> | <b>4.80</b> |
|-------------------|-------------|
| 10 FR             | 3400        |
| 25 FR             | 2890        |
| 30 FR             | 2720        |
| 40 FR             | 2430        |
| 10 DW             | 2380        |
| 25 DW             | 2025        |
| 30 DW             | 1905        |
| 40 DW             | 1700        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.