

# FLOTATION 648

|                           |                            |
|---------------------------|----------------------------|
| <b>TYRE SIZE</b>          | 500/55 - 20                |
| <b>UM</b>                 | IS STANDARD                |
| <b>CONSTRUCTION</b>       | BIAS                       |
| <b>MACHINERY</b>          | HAY HARVESTER / IMPLEMENTS |
| <b>VERSION</b>            | STANDARD                   |
| <b>TYRE TYPE</b>          | TL                         |
| <b>LI/SS DRIVE WHEEL</b>  | 138 A8/134 B               |
| <b>LI/SS FREE ROLLING</b> | 150 A8/146 B               |



## DIMENSIONS IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 508  | <b>RIM REC</b> | 16.00           |
| <b>OD (MM)</b>  | 1058 | <b>ECE</b>     | E11-106R-003369 |
| <b>SLR (MM)</b> | 458  | <b>PR</b>      | 12              |
| <b>RC (MM)</b>  | 3153 |                |                 |

## LOAD CAPACITY (KG/TYRE)

| KM/H / BAR | 2.00 | 2.20 | 2.40 |
|------------|------|------|------|
| 10 FR      | 4215 | 4460 | 4690 |
| 20 FR      | 3795 | 4015 | 4220 |
| 30 FR      | 3370 | 3565 | 3750 |
| 40 FR      | 3010 | 3185 | 3350 |
| 50 FR      | 2710 | 2865 | 3000 |
| 10 DW      | 2970 | 3145 | 3305 |
| 20 DW      | 2670 | 2830 | 2975 |
| 30 DW      | 2375 | 2515 | 2645 |
| 40 DW      | 2120 | 2245 | 2360 |
| 50 DW      | 1910 | 2020 | 2120 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.