


# FL 630 SUPER

<b>TIRE SIZE</b>	<b>750/60 R 26.5</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	SPARGITORE / AUTOBOTTE / RIMORCHIO / ATTREZZI AGRICOLI
<b>VERSIONE</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	180 D



## DIMENSIONI IS STANDARD

<b>SW (MM)</b>	754	<b>RIM REC</b>	AG 24.00
<b>OD (MM)</b>	1574	<b>ECE</b>	E4-106R-001427
<b>SLR (MM)</b>	694	<b>SRI</b>	725
<b>RC (MM)</b>	4800		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	2340	2705	3070	3725	4310	4965	5625	6060	6720	7300
65	2560	2960	3360	4080	4720	5440	6160	6640	7360	8000
50	3100	3585	4070	4940	5715	6585	7455	8035	8910	9680
40	3485	4030	4570	5550	6420	7400	8380	9035	10010	10880
25	4045	4680	5310	6450	7460	8600	9735	10495	11630	12640
10	4610	5330	6050	7345	8500	9795	11090	11955	13250	14400

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.