


# EARTHMAX SR 22

<b>TIRE SIZE</b>	<b>20.5 R 25</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	VÄGHYVLARE / HJULLASTARE / BULLDOZER / HJULLASTARE / BULLDOZER / VÄGHYVLARE
<b>VERSION</b>	CUT RESISTANT COMPOUND
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	177 B ; 193 A2



## DIMENSIONER IS STANDARD

<b>OD (MM)</b>	1490	<b>RIM ALT</b>	17.00/1.7
<b>SLR (MM)</b>	640	<b>TRA CODE</b>	E2/L2
<b>RC (MM)</b>	4315	<b>STAR RATING</b>	★★
<b>RIM REC</b>	17.00/2.0		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	4.00	4.25	4.50	4.75	5.00	5.25	5.50	5.75	6.00	6.25	6.50
50	5800	6150	6500	6700	6900	7300	-	-	-	-	-
10	-	-	-	-	-	9750	10000	10300	10900	11200	11500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.