


# BK-LOADER 53

|                     |  |
|---------------------|--|
| <b>TYRE SIZE</b>    | <b>405/70 R 18</b>   |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | LOADER   |
| <b>VERSION</b>      | ARAMID BELTED  |
| <b>TYRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 153A2/149A4  |



## DIMENSIONS IS STANDARD

|                |                       |
|----------------|-----------------------|
| <b>SW (MM)</b> | 407                   |
| <b>OD (MM)</b> | 1045                  |
| <b>RIM REC</b> | 13                    |
| <b>RIM ALT</b> | 14; 13 SDC; 12;12 SDC |

## LOAD CAPACITY (KG/TYRE)

| KM/H / BAR          | 1.5  | 2.0  | 2.5  | 3.0  | 3.5  | 4.0  | 4.5  | 5.0  | 5.5  |
|---------------------|------|------|------|------|------|------|------|------|------|
| <b>20 TRANSPORT</b> | 1140 | 1465 | 1725 | 1985 | 2275 | 2505 | 2765 | 2990 | 3250 |
| <b>10 LOADING</b>   | 1280 | 1645 | 1935 | 2230 | 2555 | 2815 | 3105 | 3360 | 3650 |
| <b>STATIC</b>       | 2050 | 2635 | 3105 | 3570 | 4095 | 4505 | 4975 | 5385 | 5850 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.