


AGRIMAX SPARGO

| | |
|--------------|--|
| TIRE SIZE | VF 480/95 R 50 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRACTOR |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 181 D |



DIMENSIONS US STANDARD

| | | | |
|----------|----------|---------|------------------|
| USA CODE | 94075638 | RC (IN) | 260.1 |
| SW (IN) | 18.9 | RIM REC | DW 16 L |
| OD (IN) | 85.9 | RIM ALT | DW 15 L |
| SLR (IN) | 39.0 | ECE | E11-106R-0010083 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 14 | 17 | 20 | 23 | 26 | 29 | 32 | 35 | 38 | 41 | 44 | 46 |
|---------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 45 | 8920 | 9930 | 11100 | 12120 | 12790 | 13290 | 13790 | 14300 | 14970 | 15650 | 16150 | 16830 |
| FROM 40 TO 25 | 9650 | 10730 | 12010 | 13100 | 13830 | 14370 | 14920 | 15470 | 16200 | 16920 | 17460 | 18190 |
| 20 | 9840 | 10940 | 12240 | 13360 | 14110 | 14650 | 15220 | 15780 | 16520 | 17260 | 17820 | 18560 |
| 12 | 10040 | 11160 | 12480 | 13630 | 14390 | 14940 | 15510 | 16090 | 16840 | 17600 | 18170 | 18920 |
| 5 | 10610 | 11800 | 13200 | 14410 | 15220 | 15800 | 16410 | 17010 | 17810 | 18610 | 19220 | 20010 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.