


AGRIMAX SPARGO

TIRE SIZE	VF 380/105 R 54
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRACTOR
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	180 D



ABMESSUNGEN IS STANDARD

SW (MM)	400	RIM REC	W 13 A
OD (MM)	2140	RIM ALT	W 12; DW 12; DW 13; DW 13 L
SLR (MM)	984	ECE	E11-106R-0010148
RC (MM)	6503	SRI	1025

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.2	1.4	1.6	1.8	2	2.2	2.4	2.6	2.8	3	3.2	3.4	3.6	3.8	4	4.2	4.4
70	3495	3930	4295	4515	4730	4875	5020	5275	5530	5750	5970	6330	6405	6550	6695	6985	7275
FROM 65 TO 40	3840	4320	4720	4960	5200	5360	5520	5800	6080	6320	6560	6960	7040	7200	7360	7680	8000
30	3920	4410	4815	5060	5305	5470	5635	5920	6205	6450	6695	7100	7185	7345	7510	7835	8160
20	3995	4495	4910	5160	5410	5575	5745	6035	6325	6575	6825	7240	7325	7490	7655	7990	8320
10	4225	4755	5195	5460	5720	5900	6075	6380	6690	6955	7220	7660	7745	7920	8100	8450	8800

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.