


AGRIMAX V- FLECTO

TIRE SIZE	VF 900/60 R 42 CFO
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	ТРАКТОР-ТЯГАЧ / ТРАКТОР ВЫСОКОЙ МОЩНОСТИ
VERSION	SPECIAL
TIRE TYPE	TL
LI/SS	189 D



РАЗМЕРЫ IS STANDARD

SW (MM)	900	RIM REC	DW 30B
OD (MM)	2142	ECE	E11-106R-006165
SLR (MM)	931	SRI	1025
RC (MM)	6390		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1	1.2	1.4	1.6	2
70	4590	5340	6180	6930	7680	8435	9370
FROM 65 TO 40	5045	5870	6795	7620	8445	9270	10300
30	5145	5985	6930	7770	8610	9455	10505
20	5245	6100	7065	7920	8780	9640	10710
10	5545	6455	7470	8380	9285	10195	11330
UPTO 30 CYC	5730	6665	7720	8655	9590	10525	11690
UPTO 15 CYC	6840	7955	9215	10330	11445	12560	13955
UPTO 10 CYC	7495	8720	10095	11320	12545	13770	15295
10 HT	5145	5985	6930	7770	8610	9455	10505

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.