


FL 630 SUPER

TIRE SIZE	750/60 R 26.5
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	STREUMASCHINE / TANKWAGEN / ANHÄNGER / LANDWIRTSCHAFTLICHE GERÄTE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	180 D



ABMESSUNGEN US STANDARD

USA-CODE	94042135	RC (IN)	189.0
SW (IN)	29.7	RIM REC	AG 24.00
OD (IN)	62.0	ECE	E4-106R-001427
SLR (IN)	27.3		

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	15	17	23	29	35	41	46	52	58
45	5160	5960	6770	8210	9500	10950	12400	13360	14810	16090
40	5640	6530	7410	8990	10410	11990	13580	14640	16230	17640
30	6830	7900	8970	10890	12600	14520	16430	17710	19640	21340
25	7680	8880	10070	12230	14150	16310	18470	19920	22070	23980
15	8920	10320	11710	14220	16450	18960	21460	23140	25640	27860
5	10160	11750	13340	16190	18740	21590	24450	26350	29210	31740

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.