

# TR 135

|                     |                      |
|---------------------|----------------------|
| <b>TIRE SIZE</b>    | <b>12.4 - 38</b>     |
| <b>UM</b>           | US STANDARD          |
| <b>CONSTRUCTION</b> | ⊠ BIAS               |
| <b>MACHINERY</b>    | TRATTORE / RIMORCHIO |
| <b>VERSIONE</b>     | STANDARD             |
| <b>TIRE TYPE</b>    | TT                   |
| <b>LI/SS</b>        | 124 A8               |



## DIMENSIONI US STANDARD

|                   |          |                |                |
|-------------------|----------|----------------|----------------|
| <b>CODICE USA</b> | 94032693 | <b>RC (IN)</b> | 183.9          |
| <b>SW (IN)</b>    | 12.8     | <b>RIM REC</b> | W 11           |
| <b>OD (IN)</b>    | 60.0     | <b>RIM ALT</b> | W 9; W 10      |
| <b>SLR (IN)</b>   | 28.3     | <b>ECE</b>     | E4-106R-002038 |

## LOAD CAPACITY (LBS/TIRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>32</b> |
| 25               | 3520      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.