DATA SHEET

PRINTED ON
23-04-2026

EARTHMAX SR 44

TIRE SIZE	**325/95 R 24**
UM	US STANDARD
CONSTRUCTION	RADIAL
MACHINERY	CAMIÃO BASCULANTE
VERSÃO	STANDARD
TIRE TYPE	TL
LI/SS	158 B

DIMENSÕES US STANDARD

CÓDIGO USA	94054282	**RIM REC**	8.50V
OD (IN)	49.2	**RIM ALT**	9.00V
SLR (IN)	22.6	**TRA CODE**	E4
RC (IN)	149.2	**STAR RATING**	★★★

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	65	69	73	76	80	83	87	91	94	98	102
30	6800	6950	7400	7600	7850	8050	8250	8550	8800	9100	9350

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..