


# MULTIMAX MP 527

<b>TIRE SIZE</b>	<b>360/70 R 18 IND</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	КОМПАКТНЫЙ ПОГРУЗЧИК / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / КОМПАКТНЫЙ ПОГРУЗЧИК / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	142 A8/B



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94053650	<b>RC (IN)</b>	113.7
<b>SW (IN)</b>	14.2	<b>RIM REC</b>	11
<b>OD (IN)</b>	38.1	<b>RIM ALT</b>	W10; 11 SDC; W11; 12; 12 SDC
<b>SLR (IN)</b>	17.3	<b>ECE</b>	E11-106R-002996

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	23	29	35	41	46	51	58	61	64
30	2810	3340	3800	4330	4850	5200	5840	-	-
25	2810	3340	3800	4330	4850	5200	5840	-	-
20	3010	3570	4080	4640	5200	5580	6260	-	-
15	3120	3700	4220	4810	5390	5790	6490	-	-
5 CYC.	3430	4210	4960	5700	6490	7050	7980	8420	8760
STATIC	5250	6460	7590	8740	9950	10820	12230	12910	13440

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.