

# FL 630 SUPER

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>710/50 R 30.5</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | MAȘINĂ DE ÎMPRĂȘTIAT / CISTERNĂ /<br>REMORCĂ / MAȘINI DE<br>IMPLEMENTARE                 |
| <b>VERSION</b>      | STEEL BELTED   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 173 D  |



## DIMENSIUNI US STANDARD

|                 |          |                |                  |
|-----------------|----------|----------------|------------------|
| <b>USA CODE</b> | 94506293 | <b>RC (IN)</b> | 179.1            |
| <b>SW (IN)</b>  | 27.0     | <b>RIM REC</b> | AG 20.00         |
| <b>OD (IN)</b>  | 58.5     | <b>RIM ALT</b> | AG 24.00         |
| <b>SLR (IN)</b> | 26.6     | <b>ECE</b>     | E11-106R-0010340 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 14   | 12   | 20    | 23    | 26    | 29    | 32    | 35    | 38    | 41    |
|-----------|------|------|-------|-------|-------|-------|-------|-------|-------|-------|
| 45        | 4050 | 4700 | 5360  | 6660  | 7570  | 8870  | 9920  | 10820 | 11870 | 13040 |
| 40        | 4440 | 5160 | 5870  | 7310  | 8310  | 9740  | 10890 | 11890 | 13040 | 14330 |
| 30        | 5380 | 6250 | 7110  | 8850  | 10060 | 11790 | 13180 | 14400 | 15780 | 17340 |
| 25        | 6050 | 7020 | 7990  | 9940  | 11310 | 13260 | 14810 | 16180 | 17740 | 19490 |
| 15        | 7020 | 8160 | 9290  | 11550 | 13140 | 15400 | 17220 | 18790 | 20610 | 22640 |
| 5         | 8000 | 9290 | 10580 | 13160 | 14970 | 17550 | 19610 | 21420 | 23480 | 25790 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.