

# EARTHMAX SR 46

|              |                                                                                          |
|--------------|------------------------------------------------------------------------------------------|
| TIRE SIZE    | 30.00 R 51                                                                               |
| UM           | US STANDARD                                                                              |
| CONSTRUCTION |  RADIAL |
| MACHINERY    | AUTOBASCULANTĂ RIGIDĂ                                                                    |
| VERSION      | STANDARD COMPOUND                                                                        |
| TIRE TYPE    | TL                                                                                       |
| LI/SS        | 230 B                                                                                    |



## DIMENSIUNI US STANDARD

|          |          |             |           |
|----------|----------|-------------|-----------|
| USA CODE | 94074754 | RIM REC     | 22.00/4.5 |
| OD (IN)  | 114.0    | TRA CODE    | E4        |
| SLR (IN) | 51.2     | STAR RATING | ★★        |
| RC (IN)  | 346.5    |             |           |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 73    | 76    | 80    | 83    | 87    | 91    | 94    | 98    | 102   |
|-----------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 30        | 56800 | 58400 | 61500 | 64000 | 66000 | 68000 | 69500 | 71500 | 74000 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.