

# AGRIMAX RT 765

|                  |                                                                       |
|------------------|-----------------------------------------------------------------------|
| <b>TIRE SIZE</b> | <b>420/70 R 24</b>                                                    |
| <b>UM</b>        | US STANDARD                                                           |
| <b>MACHINERY</b> | SPRAYER / TRACTOR / VINEYARD<br>HARVESTER / HARVESTER /<br>IMPLEMENTS |
| <b>VERSION</b>   | STANDARD                                                              |
| <b>TL/TT</b>     | TL                                                                    |
| <b>LI/SS</b>     | 130 D                                                                 |



## DIMENSIONS US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA CODE</b> | 94063024 | <b>RC (IN)</b> | 144.9           |
| <b>SW (IN)</b>  | 16.5     | <b>RIM REC</b> | W 13            |
| <b>OD (IN)</b>  | 49.1     | <b>RIM ALT</b> | W 12 ; W 14 L   |
| <b>SLR (IN)</b> | 21.8     | <b>ECE</b>     | E11-106R-005826 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI   | 9    | 12   | 15   | 17   | 20   | 23   |
|-------------|------|------|------|------|------|------|
| <b>40</b>   | 2300 | 2690 | 3060 | 3440 | 3810 | 4190 |
| <b>30</b>   | 2420 | 2820 | 3220 | 3620 | 4010 | 4400 |
| <b>25</b>   | 2540 | 2940 | 3360 | 3770 | 4190 | 4600 |
| <b>20</b>   | 2660 | 3090 | 3530 | 3960 | 4390 | 4820 |
| <b>5 LT</b> | 3100 | 3600 | 4110 | 4620 | 5130 | 5620 |
| <b>5 HT</b> | 2660 | 3090 | 3530 | 3960 | 4390 | 4820 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.