


# AT 603

<b>TIRE SIZE</b>	<b>12.5/80 -18</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	MAQUINARIA AGRÍCOLA / MAQUINARIA AGRÍCOLA / CARGADORA RETROEXCAVADORA / CARGADORA RETROEXCAVADORA
<b>VERSIÓN</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	129 A8
<b>LI/SS FREE ROLLING</b>	142 A8



## DIMENSIONES IS STANDARD

<b>SW (MM)</b>	308	<b>RIM REC</b>	W 9
<b>OD (MM)</b>	1000	<b>RIM ALT</b>	11
<b>SLR (MM)</b>	448	<b>PR</b>	12
<b>RC (MM)</b>	3027	<b>SRI</b>	475

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	3.70
10 FR	3710
25 FR	3155
30 FR	2970
40 FR	2650
10 DW	2590
25 DW	2200
30 DW	2070
40 DW	1850

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.