


# AS 504

|                           |   |
|---------------------------|---|
| <b>TIRE SIZE</b>          | <b>6.5/80 - 12</b>  |
| <b>UM</b>                 | IS STANDARD   |
| <b>CONSTRUCTION</b>       |  BIAS                    |
| <b>MACHINERY</b>          | LEVANTADOR TELESCÓPICO /<br>REBOQUE PARA OS CAMPOS /<br>IMPLEMENTOS AGRÍCOLAS /<br>LEVANTADOR TELESCÓPICO |
| <b>VERSÃO</b>             | STANDARD  |
| <b>TIRE TYPE</b>          | TL  |
| <b>LI/SS DRIVE WHEEL</b>  | 72 A8   |
| <b>LI/SS FREE ROLLING</b> | 84 A8   |



## DIMENSÕES IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 169  | <b>RIM REC</b> | 5 J             |
| <b>OD (MM)</b>  | 608  | <b>RIM ALT</b> | 5 JA            |
| <b>SLR (MM)</b> | 283  | <b>ECE</b>     | E11-106R-003440 |
| <b>RC (MM)</b>  | 1836 | <b>PR</b>      | 4               |

## LOAD CAPACITY (KG/TIRE)

| <b>KM/H / BAR</b> | <b>2.40</b> |
|-------------------|-------------|
| 10 FR             | 700         |
| 25 FR             | 595         |
| 30 FR             | 560         |
| 40 FR             | 500         |
| 10 DW             | 495         |
| 25 DW             | 420         |
| 30 DW             | 400         |
| 40 DW             | 355         |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.