

# RIB F3

|                     |   |
|---------------------|---|
| <b>TIRE SIZE</b>    | 9.00 - 16                                       |
| <b>UM</b>           | IS STANDARD                                     |
| <b>CONSTRUCTION</b> |   |
| <b>MACHINERY</b>    | 2WD TRACTOR / TRAILER / TRACTOR /<br>IMPLEMENTS |
| <b>VERSION</b>      | STANDARD  |
| <b>TIRE TYPE</b>    | TL  |
| <b>LI/SS</b>        | 120 A6 ; 112 A8                                 |



## DIMENSIONS IS STANDARD

|                 |      |                |                    |
|-----------------|------|----------------|--------------------|
| <b>SW (MM)</b>  | 245  | <b>RIM REC</b> | W 8                |
| <b>OD (MM)</b>  | 878  | <b>RIM ALT</b> | 6.00 F; W 7; W 8 L |
| <b>SLR (MM)</b> | 387  | <b>ECE</b>     | E11-106R-004592    |
| <b>RC (MM)</b>  | 2573 | <b>PR</b>      | 12                 |

## LOAD CAPACITY (KG/TIRE)

| <b>KM/H / BAR</b> | <b>4.70</b> |
|-------------------|-------------|
| 30                | 1400        |
| 40                | 1120        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.