

# AGRIMAX RT 765

|                  |                                                                                                    |
|------------------|----------------------------------------------------------------------------------------------------|
| <b>TIRE SIZE</b> | <b>710/70 R 38</b>                                                                                 |
| <b>UM</b>        | IS STANDARD                                                                                        |
| <b>MACHINERY</b> | FELDSPRITZE / TRACTOR /<br>TRAUBENERNTEMASCHINE /<br>ERNTEMASCHINE /<br>LANDWIRTSCHAFTLICHE GERÄTE |
| <b>VERSION</b>   | SPECIAL                                                                                            |
| <b>TIRE TYPE</b> | TL                                                                                                 |
| <b>LI/SS</b>     | 175 D ; 178 A8                                                                                     |



## ABMESSUNGEN IS STANDARD

|                 |      |                 |                 |
|-----------------|------|-----------------|-----------------|
| <b>SW (MM)</b>  | 716  | <b>RIM REC</b>  | DW 23 B         |
| <b>OD (MM)</b>  | 1959 | <b>ECE</b>      | E11-106R-006000 |
| <b>SLR (MM)</b> | 859  | <b>SRI</b>      | 925             |
| <b>RC (MM)</b>  | 5751 | <b>TRA CODE</b> | R1W             |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR   | 0.6  | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  | 2.0  | 2.4  | 2.8  | 3.2  |
|--------------|------|------|------|------|------|------|------|------|------|------|
| <b>65</b>    | 2695 | 3175 | 3660 | 4075 | 4555 | 4970 | 5455 | 5865 | 6420 | 6900 |
| <b>50</b>    | 2830 | 3335 | 3840 | 4275 | 4785 | 5220 | 5725 | 6160 | 6740 | 7245 |
| <b>40</b>    | 2925 | 3450 | 3975 | 4425 | 4950 | 5400 | 5925 | 6375 | 6975 | 7500 |
| <b>30</b>    | 3095 | 365  | 4210 | 4685 | 5240 | 5715 | 6270 | 6745 | 7380 | 7935 |
| <b>10 LT</b> | 3610 | 4255 | 4905 | 5460 | 6105 | 6660 | 7310 | 7865 | 8605 | 9250 |
| <b>10 HT</b> | 3095 | 3655 | 4210 | 4685 | 5240 | 5715 | 6270 | 6745 | 7380 | 7935 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.