


MULTIMAX MP 527

TYRE SIZE	400/70 R 20 IND
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	COMPACT LOADER / TELEHANDLER / COMPACT LOADER / TELEHANDLER
VERSION	STANDARD
TL/TT	TL
LI/SS	149 A8/B



DIMENSIONS IS STANDARD

SW (MM)	404	RIM REC	13
OD (MM)	1068	RIM ALT	12 SDC ; 13 SDC ; 14
SLR (MM)	494	ECE	E4-106R-002656
RC (MM)	3282	SRI	525

LOAD CAPACITY (KG/TYRE)

KM/H / BAR	1.6	2.0	2.4	2.8	3.2	3.5	4.0	4.2	4.4
50	1560	1855	2115	2405	2700	2895	3250	-	-
40	1560	1855	2115	2405	2700	2895	3250	-	-
30	1675	1985	2265	2580	2890	3100	3480	-	-
25	1735	2060	2350	2675	3000	3215	3610	-	-
10 CYC.	1905	2340	2755	3170	3610	3925	4440	4680	4875
STATIC	2920	3590	4225	4860	5535	6020	6805	7180	7475

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.