


MULTIMAX MP 527

| | |
|---------------------|--|
| TIRE SIZE | 340/80 R 20 IND |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | KOMPAKTLADER / TELESKOPLADER / KOMPAKTLADER / TELESKOPLADER |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 144 A8/B |



ABMESSUNGEN US STANDARD

| | | | |
|-----------------|----------|----------------|------------------------------|
| USA-CODE | 94053452 | RC (IN) | 125.0 |
| SW (IN) | 13.5 | RIM REC | 11 |
| OD (IN) | 41.4 | RIM ALT | W10; 11 SDC; W11; 12; 12 SDC |
| SLR (IN) | 19.0 | ECE | E11-106R-003957 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 23 | 29 | 35 | 41 | 46 | 51 | 58 | 61 | 64 |
|-----------|------|------|------|------|-------|-------|-------|-------|-------|
| 30 | 2970 | 3530 | 4010 | 4570 | 5130 | 5500 | 6170 | - | - |
| 25 | 2970 | 3530 | 4010 | 4570 | 5130 | 5500 | 6170 | - | - |
| 20 | 3170 | 3770 | 4300 | 4890 | 5490 | 5890 | 6610 | - | - |
| 15 | 3300 | 3910 | 4460 | 5080 | 5700 | 6110 | 6860 | - | - |
| 5 CYC. | 3620 | 4450 | 5240 | 6020 | 6860 | 7460 | 8430 | 8900 | 9260 |
| STATIC | 5540 | 6820 | 8020 | 9240 | 10520 | 11430 | 12930 | 13630 | 14200 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.