

# AGRIMAX RT 855

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>320/85 R 34</b>   |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | IRRORAZIONE / VENDEMMIATRICE /<br>TRATTORE / MIETITREBBIA / ATTREZZI<br>AGRICOLI         |
| <b>VERSIONE</b>     | SPECIAL  |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 141 A8/B   |



## DIMENSIONI IS STANDARD

|                 |      |                |                |
|-----------------|------|----------------|----------------|
| <b>SW (MM)</b>  | 329  | <b>RIM REC</b> | W 11           |
| <b>OD (MM)</b>  | 1408 | <b>RIM ALT</b> | W 9 ; W 10     |
| <b>SLR (MM)</b> | 645  | <b>ECE</b>     | E4-106R-000758 |
| <b>RC (MM)</b>  | 4280 | <b>SRI</b>     | 675            |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6  | 0.8  | 1.2  | 1.6  | 2.0  | 2.4  | 2.8  | 3.2  | 3.6  |
|------------|------|------|------|------|------|------|------|------|------|
| 50         | 930  | 1085 | 1420 | 1730 | 1880 | 2010 | 2190 | 2370 | 2575 |
| 40         | 930  | 1085 | 1420 | 1730 | 1880 | 2010 | 2190 | 2370 | 2575 |
| 30         | 995  | 1160 | 1520 | 1850 | 2015 | 2155 | 2350 | 2540 | 2760 |
| 10 LT      | 1245 | 1455 | 1905 | 2315 | 2525 | 2695 | 2940 | 3180 | 3455 |
| 10 HT      | 995  | 1160 | 1520 | 1850 | 2015 | 2155 | 2350 | 2540 | 2760 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.