DATA SHEET

PRINTED ON
22-04-2026

EARTHMAX SR 51 SP

TIRE SIZE	**35/65 R 33**
UM	IS STANDARD
CONSTRUCTION	RADIAL
MACHINERY	PALA CARGADORA / BULDÓCER
VERSIÓN	CUT RESISTANT COMPOUND
TIRE TYPE	TL
LI/SS	229 A2

DIMENSIONES IS STANDARD

OD (MM)	2061	**TRA CODE**	L5
SLR (MM)	872	**STAR RATING**	★★★
RC (MM)	6082		
RIM REC	28.00/3.5		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	6.75	7.00	7.25	7.50	7.75	8.00
10	29000	30000	30750	31500	32000	32500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..