

# PL 801

<b>TIRE SIZE</b>	7.00 - 15
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	BIAS
<b>MACHINERY</b>	MIETITREBBIA / ATTREZZI AGRICOLI / RANGHINATORE / CARRELLO ELEVATORE / MIETITREBBIA / CARRELLO ELEVATORE
<b>VERSIONE</b>	STANDARD
<b>TIRE TYPE</b>	TT



## DIMENSIONI US STANDARD

<b>CODICE USA</b>	94007349	<b>RC (IN)</b>	0
<b>SW (IN)</b>	8.1	<b>RIM REC</b>	6.0
<b>OD (IN)</b>	30.5	<b>RIM ALT</b>	5.50 BD ; 5.5
<b>SLR (IN)</b>	0	<b>PR</b>	12

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	125	130
15 LOAD WHEEL	6245	-
15 STEER WHEEL	5275	-
5 OTHER VEHICLES	5275	-
15 OTHER VEHICLES	3885	-
STATIC SIDE LOADER	-	8520

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.