

# AS 504

<b>TIRE SIZE</b>	7.50 - 16
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	❖ BIAS
<b>MACHINERY</b>	TELESKOPLASTARE / ÅKERSLÄP / ARBETSFORDON / TELESKOPLASTARE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TT
<b>LI/SS DRIVE WHEEL</b>	92 A8
<b>LI/SS FREE ROLLING</b>	104 A8



## DIMENSIONER IS STANDARD

<b>SW (MM)</b>	209	<b>RIM REC</b>	5.50 F
<b>OD (MM)</b>	803	<b>RIM ALT</b>	4.50 E; 5.00 F; 4.00 E; 5 K; 6 LB; 6.00 F
<b>SLR (MM)</b>	372	<b>PR</b>	6
<b>RC (MM)</b>	2475	<b>SRI</b>	390

## LOAD CAPACITY (KG/TIRE)

<b>KM/H / BAR</b>	<b>2.30</b>
10 FR	1260
25 FR	1070
30 FR	1010
40 FR	900
10 DW	880
25 DW	750
30 DW	705
40 DW	630

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.