


# MULTIMAX MP 529



<b>TIRE SIZE</b>	<b>340/80 R 18</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TELEHANDLER
<b>VERSION</b>	STEEL BELTED
<b>TL/TT</b>	TL
<b>LI/SS</b>	143 A8/B

## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	343	<b>RIM REC</b>	11 ; 11 SDC ; W 11
<b>OD (MM)</b>	1001	<b>RIM ALT</b>	W 10 ; 12 ; 12 SDC
<b>SLR (MM)</b>	445	<b>ECE</b>	E11-106R-002972
<b>RC (MM)</b>	3007	<b>SRI</b>	475

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.6	2.0	2.4	2.8	3.2	3.5	4.0	4.2	4.4
<b>50</b>	1310	1555	1775	2020	2265	2430	2725	-	-
<b>40</b>	1310	1555	1775	2020	2265	2430	2725	-	-
<b>30</b>	1405	1665	1900	2165	2425	2600	2920	-	-
<b>25</b>	1455	1725	1970	2240	2515	2695	3025	-	-
<b>10 CYC.</b>	1600	1965	2315	2660	3030	3295	3725	3930	4090
<b>STATIC</b>	2450	3010	3545	4080	4640	5050	5710	6020	6270

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.